

**NEW PRODUCT
CATALOGUE
2023-2024**



AFFORDABILITY MEETS DURABILITY



Innovation never stops

Guided by Japanese design principles, every element of our product is chosen to improve performance, balance, usability, longevity & control. Attention to details that ensures the professional in finishing every single job as easy as possible. That's what drives us & keeps us one step ahead.

Safety

Double-Insulation power tool, indicated by the double square mark (□) can be operated without external grounding. All HiKOKI power tools are designed and manufactured considering safety and usability.

General precautions

1. Read and follow handling instructions provided with the power tool and comply with all the operating instructions and warnings.
2. Never let children use the power tool.
3. Keep others, especially children, away from the tool.
4. Wear eye protector to protect the eyes.
5. Never touch blades or cutters during operation.
6. Avoid unintentional contact with the power switch when the tool is connected to a power source.
7. To ensure proper function of the tool, DO NOT remove installed covers or screws. DO NOT modify components and parts.
8. Prior to operation, carefully inspect the tool to ensure all the parts properly functioning.
9. Immediately stop operation if abnormalities are noted.
10. Ensure that motor ventilation opening is kept fully open.
11. Always keep the blades and cutters sharp and clean.
12. Have the power tool inspected at a proper regular interval by an authorized Service Center.
13. Maintain the proper care and cleanliness of the power tool.
14. Consult an authorised Service Center for repair and/or part replacement.
15. DO NOT use the power tool for any other application than those specified in the handling instructions.
16. DO NOT use the tool for work beyond its prescribed capability.
17. To avoid possible electric shock, DO NOT use the power tool in wet areas.
18. Ensure that the applied voltage is the same as that specified on the nameplate.
19. Ensure that electric plug is plugged into a matching receptacle that is properly installed and grounded in accordance with the instruction manual, all applicable local codes, and ordinances, except for double insulated tools.
20. Ensure that the power supply is disconnected after operation.
21. DO NOT lift the power tool with the cord or remove the plug from the receptacle by pulling the cord.
22. Always handle the power tool with care.
23. Proper posture is essential for safe operation.
24. Dress properly and work in proper clothing and shoes.
25. Always keep the work area in good order.
26. When not in use, store the power tool.
27. DO NOT stare into LASER beam.

Icons

-  Double Insulation
-  Variable Speed
-  2-speed Gear
-  Reversible
-  SDS max Shank
-  SDS-plus Shank
-  Hex Shank
-  Hex Shank

Drill



HMD 6A | P-3

Impact Drill



HMDV 13A | P-3

Disc Grinder



HMG 10A | P-4



HMG 13A | P-4

Die Grinder



HMGP 3A | P-5

Hammer Drill



HMDH 20A | P-5

Demolition Hammer



HMM 60A | P-6

Blower



HMRB 30A | P-6

Marble Cutter



HMCM 4A | P-7



HMCM 5A | P-7

Trimmer



HMM 6A | P-8

Planer



HMP 20A | P-8

6.5mm
Drill
HMD6A

Features

- ▶ Variable Speed Control Switch
- ▶ Reversible Running.



Specifications

HMD6A

Capacity	Wood	Maxø 15mm
	Steel	Maxø 6.5mm
Power Input	320w	
No-Load Speed	0 - 4,200/min.	
Overall Length	210mm	
Weight	0.9kg	



13mm
Impact Drill
HMDV 13A

Features

- ▶ Powerful Motor
- ▶ Soft Grip For Comfort Operation.



Specifications

HMDV 13A

Capacity	Concrete	13mm
	Steel	13mm
	Wood	25mm
Full Load Impact Rate	48,000/min.	
Power Input	550w	
No-Load Speed	0 - 3,000/min.	
Overall Length	295mm	
Weight	1.8kg	



100mm

Disc Grinder HMG 10A

Features

- ▶ Slide Switch.
- ▶ Compact & Light Weight.



Specifications

HMG 10A

Wheel Dia.	100 mm
Spindle Thread	M10
Power Input	600w
No-Load Speed	12000/min
Overall Length	271mm
Weight	1.7 kg



125mm

Disc Grinder HMG 13A

Features

- ▶ Slide Switch.
- ▶ Compact & Light Weight.



Specifications

HMG 13A

Wheel Dia.	125mm
Spindle Thread	M14
Power Input	880w
No-Load Speed	11,000/min
Overall Length	271mm
Weight	1.8kg



25mm

Die Grinder HMGP 3A

Features

- ▶ 6mm Collet With Snap Switch.
- ▶ Longer Nose To Reach, In Depth Deburring.
- ▶ High Speed Motor.



Specifications

HMGP 3A	
Wheel Dia.	25mm
Hand Capacity	6mm
Power Input	550w
No-Load Speed	34,000/min
Overall Length	379mm
Weight	1.7kg



20mm

Hammer Drill HMDH 20A

Features

- ▶ 2 Mode With Variable Speed.
- ▶ Equipped With 550w Motor.
- ▶ Compact & Light Weight.



Specifications

HMDH 20A	
Capacity	Concrete 20mm
	Steel 13mm
	Wood 32mm
Power Input	550w
Bit Shank	SDS plus
No-Load Speed	0-1,250/min
Weight	2.6Kg



Demolition Hammer

HMH 60A



Features

- ▶ 2 Mode With Variable Speed.
- ▶ Equipped With 550w Motor.
- ▶ Compact & Light Weight.
- ▶ Soft Grip Handle.

Specifications

HMH 60A

Power Input	1,500 w
Impact Rate	1,000 - 2,050/min
Overall Length	594 mm
Weight	10.6 kg

Blower

HMRB 30A



Features

- ▶ Variable Speed With Dial Control.

Specifications

HMRB 30A

Air Velocity (with Nozzle)	0 - 89 m/s
Volume Flow (without Nozzle)	0 - 3.4 m³/min
Power Input	550 w
No -Load Speed	0 - 16,000 /min.
Overall Length	493 mm
Weight	1.7 kg

110mm
Cutter
HMCM 4A



Features

- ▶ Powerful Motor.
- ▶ Dust Proof Switch.

Specifications

HMCM 4A

Wheel Dia.	110mm
Max. Cutting Depth	32mm
Power Input	1,300w
No-Load Speed	13,000/min
Overall Length	215.5mm
Weight	3.1kg



125mm
Cutter
HMCM 5A



Features

- ▶ Powerful Motor.
- ▶ Dust Proof Switch.

Specifications

HMCM 5A

Wheel Dia.	125mm
Max. Cutting Depth	39mm
Power Input	1,400w
No-Load Speed	12,000/min
Overall Length	223.5mm
Weight	3.2kg



Trimmer HMM 6A



Features

- Fine Bit Depth Adjustment

Specifications

HMM 6A

Collet Chuck	6.35 mm
Power Input	505 w
No-Load Speed	32,000 /min.
Overall Length	207 mm
Weight	1.5 kg



80mm Planer HMP 20A



Features

- Larger Trigger For Comfortable & Easy Operation.
- Robust Aluminium End Bracket.

Specifications

HMP 20A

Cutting Width	80 mm
Max. Cutting Depth	1.0 mm
Power Input	560 w
No-Load Speed	16,500 /min
Overall Length	300 mm
Weight	2.6 kg





BRANCHES

Ahmedabad	: 90999 20371
Bangalore	: 90083 04461
Bhubaneshwar	: 98302 00254
Chennai	: 94453 92512
Cochin	: 95677 61040
Delhi	: 97119 18942
Guwahati	: 98360 92333
Gurgaon	: 97111 92658
Hyderabad	: 95917 92831
Jaipur	: 88240 99593
Kolkata	: 98311 60116
Lucknow	: 90267 53265
Ludhiana	: 85910 38099
Mumbai	: 75960 26989
Pune	: 97027 86342

HiKOKI

HIGH PERFORMANCE POWER TOOLS

Head Quarter:

Koki Holdings Co., Ltd.

Shinagawa intercity Tower A, 20th floor, 15-1,
Konan 2-chrome, Minato-ku, Tokyo 108-6020,
Japan.

Tel; +81-3-5783-0601

Fax: +81-3-5783-0709

Registered & Head Office:

HiKOKI Power Tools India Pvt. Ltd.

Plot No.9A, 1st Phase, Peenya Industrial Area,
Bengaluru 560058. India.

Tel: 080-41170777/78/28396198

Fax: 080-41171222

Email: ho.mktg@hikoki-powertools.in

Website: www.hikoki-powertools.in

For any Customer Support / Service

Toll Free Number



18005725726

Timings: 10am to 6pm
Closed on Saturdays / Sunday
and Public Holidays